


Technical datasheet for:

KmR



General data

Item	Marking label with pipe plug	
Description	The marking labels with pipe plug KmR are designed to brand speedpipe with a permanent marking like Edding with the customer's address in the branch section. They are suitable for the gas- and water-tight sealing of initially unoccupied speedpipe up to 0.5 bar and can easily and fastly be installed. By breaking off the protection cap the customer's address remains on the speedpipe after having blown in a fibre optic cable.	
Package unit	40 Pcs.	
Transport and storage temperature	-40 to +65	°C
Laying or installation temperature	-10 to +50	°C
Operating temperature	-40 to +65	°C

Technical data

Quality	Value	Unit
Material	Acrylester-Styrol-Acrylnitril ASA	
Dimension	KmR 7:	d = 20; L = 122
	KmR 10:	d = 20; L = 122
	KmR 12:	d = 20; L = 122
	KmR 14:	d = 23; L = 122
	KmR 16:	d = 25; L = 122
	KmR 20:	d = 29; L = 122
Pressure	0.5	bar

gabocom ist nach dem Qualitätssicherungssystem DIN EN ISO 9001, dem Umweltmanagementsystem DIN EN ISO 14001 und dem Energiemanagementsystem DIN EN ISO 50001 zertifiziert. Die verwendeten Materialien erfüllen die REACH-Vorgabe (EU-Verordnung 1907/2006) und die RoHS-Vorgabe (EU-Richtlinien 2011/65).

gabo Systemtechnik GmbH
Am Schaidweg 7
94559 Niederwinkling
GERMANY

Tel. +49 9962 950-200
Fax +49 9962 950-202
info@gabocom.com
www.gabocom.com

Editor: CBR
Variant
Date: 09.05.2023
Edition: 4

No responsibility is taken for the currency and completeness of details and information. This document can be revised and supplemented without prior notice. Liability for damages is excluded.

